HAYBOB

300 / 360





Invest in Quality®



PRACTICAL, ECONOMICAL, **MULTI-PURPOSE MACHINES**

The HayBob 300 and 360 tedder/rake combination are universal haymakers, ideally suited for the farm hobbyist and hay producers with small- to medium-sized operations. The HayBob offers excellent performance in grass and delicate legume hay crops, and provides thorough tedding to uniformly spread wet crops for fast drying. Easily converted from tedding to raking, these machines provide gentle crop handling and produce fluffy, well-formed windrows. The HayBob provides a practical and economical alternative for producers who wish to save the cost of multiple specialized machines.



CENTRIFUGAL FORCE-CONTROLLED TINES

The centrifugal force-controlled, horizontal tines self adjust to field contours as they float through stubble to cleanly pick up crop, providing faster working speeds with little risk of contamination when tedding and raking.



HAYBOB 300

The HayBob 300 provides efficient tedding and quality centerdelivery raking. Adjustable swath boards produce neatly formed windrows and may be offset to form a double row in three passes.



PIVOTING HEADSTOCK WITH LOCK

The pivoting headstock unlocks while at work to closely follow the path of the tractor when turning, without damage to the windrow. When raised for transport, the headstock automatically centers and locks for added safety.



HAYBOB 360

The rotation of the left rotor on the HayBob 360 is easily reversed with a shift lever for simple conversion between raking and tedding. The side-delivery design produces uniform windrows and the ability to merge swaths in two passes.



MORE BENEFITS YOU CAN EXPECT

- Twenty individually mounted, pivoting tines feature nylon bearings to provide reliable performance and operation that is practically maintenance-free.
- The tine height and rotor pitch angle are quickly optimized for both tedding and raking by adjusting wheel columns and the tractor's top link to obtain the desired setting.
- Each rotor basket is equipped with both narrow and wide tines to obtain a wide working area for high-capacity operation and faster working speeds.
- A central swath divider ensures that crop is evenly distributed between the rotors when tedding to provide the most uniform distribution of crop for rapid drying.

CHOOSE THE MODEL TO MEET YOUR NEEDS

Model Specifications

	HAYBOB 300	HAYBOB 360
DIMENSIONS		
Working Width		
- Tedding	9′10″ / 3 m	9'10" / 3 m
– Single Swath Raking	9′10″ / 3 m	11′10″ / 3.6 m
– Double Swath Raking	19'8" / 6 m (3 Passes)	19'8" / 6 m (2 Passes)
Transport Width	9′2″ / 2.8 m	8′10″ / 2.7 m
SPECIFICATIONS		
Number of Rotors	2	
Number of Tines Per Rotor	10	
Raking Windrow Position	Center	Left
Attachment	Cat 1 & Cat 2	
Pivoting Headstock	Standard	
Wheel Height Adjustment	Standard	
Balloon Tires	15 X 6.0-6	
Safety Guards	Standard	
PTO Speed	350 – 540 RPM	
PTO Speed with Slip Clutch Protection	Standard	
Weight	661 lbs / 300 kg	761 lbs / 345 kg
Minimum PTO Power Requirement	15 hp / 11 kW	20 hp / 15 kW

For more information about your nearest Kuhn Knight dealer and other Kuhn Knight products, visit our website

www.KuhnNorthAmerica.com



Visit our YouTube channel to watch our latest product videos.

Your Kuhn Knight dealer



KUHN NORTH AMERICA, INC.

Corporate Headquarters 1501 West Seventh Avenue - Brodhead, WI 53520 Phone: (608) 897-2131 Fax: (608) 897-2561

Our machines comply with the North American safety regulations. In our leaflets, to better illustrate certain details of the machines some safety devices could have been removed. Conforming to the assembly and operator's manual, in no circumstances must machine be operated without these safety devices in place. All machines are equipped with safety devices which comply with the regulations of the countries in which they are delivered. In the interest of progress, we reserve the right to change without notice any specifications, design or materials listed. Patents filed in several countries.



